CASE WESTERN RESERVE
UNIVERSITY EST. 1826

Efficient bromide removal from produced water by peroxymonosulfate for controlling disinfection byproduct formation in downstream water supplies

Kuan Huang (presenter) and Huichun (Judy) Zhang*

Case Western Reserve University

March 25, 2020

Horizontal Drilling and Hydraulic Fracturing

- High pressure (480 to 850 atmosphere).

Impact of produced water discharge on water quality

Location	TDS calculated (mg/L)	Cl ⁻	Br ⁻	SO ₄ ²⁻	Alkalinity	Na ⁺	Ca ²⁺	Mg ²⁺	Ba ²⁺	Sr ²⁺
Upstream (-50m)	209	18	0.05	152	8	21	39	11	1.32	0.19
Effluent	123,500	80,500	644	1,099	254	27,300	12,600	809	13.41	1,390
Downstream (1-20m)	7,470	16,200	138	252	26	1,760	873	78	10.87	73
Downstream (20-300m)	362	195	1.39	128	3	78	65	13	0.93	2.88
Downstream (>300m)	257	88	0.52	122	3	21	40	12	1.87	0.49
Note: the data are averaged over distances and years.										

Impact of produced water on DBP formation

- Brominated species increased at the expenses of their chlorinated analogues.
- Higher produced water volume percentages resulted in larger total DBP formation.

Parker, K. M.; Zeng, T.; Harkness, J.; Vengosh, A.; Mitch, W. A. *Environ. Sci. Technol.* **2014**, 48 (19), 11161-9.

Huang, K. Z.; Xie, Y. F.; Tang, H. L. *Sci. Total Environ.* **2019**, 647, 744-751.

Selective Br⁻ removal from produced water

Low efficiency;
Complicated reaction setup.

New technology
required

Sun, M.; Lowry, G. V.; Gregory, K. B. *Water Res.* **2013**, 47 (11), 3723-31.

Objectives

- Investigate the bromide removal by PMS at different conditions;
- Develop a model to describe the processes;
- Examine the effect of produced water before and after treatment on DBP formation in impacted water supplies.

Principal pathways of bromide and chloride oxidation

Speciation

Efficient bromide oxidation by PMS

Effect of PMS amount

$[\text{Br}^-]_0 = [\text{Cl}^-]_0 = 15 \text{ mM}$; pH = 5 with 60 mM acetate buffer

Symbols – experimental data

Lines – simulation result at the same conditions

Effect of pH

$$[\text{Br}^-]_0 = [\text{Cl}^-]_0 = [\text{PMS}]_0 = 15 \text{ mM}$$

Effect of chloride concentration

Add PMS in 3 steps to minimize Cl_2 formation

Produced water: $[\text{Br}^-]_0/[\text{Cl}^-]_0 = 9.3/1840$

Symbols – experimental data

Lines – simulation result at the same conditions

Near stoichiometric PMS and acid without buffering

CSTR without buffering

Reactor volume = 200 mL prefilled with synthetic produced water and PMS (overall $[\text{PMS}] = 0.6[\text{Br}^-]$); flow rate = 3.6 mL/min; the inlet concentrations $[\text{PMS}] = 0.6[\text{Br}^-]$; additional $[\text{H}^+]$ input ≈ 2.3 mM.

DBP formation in impacted water supplies

Chlorine dose = 12 mg/L for 24 h, pH 8 with 4 mM borate buffer

Conclusion

- Bromide can be efficiently removed from produced water by PMS at weakly acidic conditions and the engineering application of such system is promising;
- The proposed model describes the reaction very well;
- The proposed method largely eliminated the enhancement of produced water on DBP formation in impacted water supplies.